	D I		D	C B				
4	Z M Lhread	ØF F F F F F F F F F F F F F F F F F F						
ω				LAYOUT SHOWN AS EXAMPLE	3			
	Keying Shown as example							
	CHARACTERISTICS-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	Connector dimensionDimNominalF19.05 MaxZ31.5 MaxVV THREADM15x1-6g			omply with by a third party notice.) diction & Control List			
N	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			FR Not Listed PN: 8D111F04PB				
	-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours			A 26-09-2016 First Release				
			ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING			
			TITLE	Aluminium Inline plu	ig 8D series			
_ _	BASIC SERIES:8D1-11FSHELL TYPE : In line Receptacle	04 P B	SCALE	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the preparts of			
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)			SOURIAU WWW.SOURIAU.COM This document is the pro SOURIAU it must not be reprodu communicated without po				
	PLATING : F = Nickel	CONTACT TIPE . FIN(5)	OUT : 11-04	SOURIAU DRG N°				
			A3	8D111F04PB-C	1/2			
	H G I	F I E	D I	C B	I A			

	т	۵	г	m	D	0
		Contact Layout				
4	- <u>×</u>	$ \begin{array}{c} $				
	Conta positic ID A B C D Shell Arrangement Numb size no. conta 11 -4 4	(mm) (mm) +.065 (1.65) +.065 (1.65) +.065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65)				
ى ن						
2						SOURIAU shall n due to a use the Specifications (professio
						P
					A 26-09-20 ISS DATE	16 First Release Latest modificatio
					Designed By:	Date:
					SCALE	
→					NA	
					SOURIA	U www.
					FORMAT A3	
	H	G	F	E	D	С

