

32P-6043-0431-9	85011-0050	no	2	----- 2	1,2,3...16	a+b
32P-6043-042V-9	85011-0036	yes	2	----- 2	1,2,3...16	a+b
32P-6043-041V-7	85011-0177	yes	1	Wire wrap 13,3	1,2,3...16	a+b
32P-6043-041V-8	85011-0165	yes	1	Wire wrap 9,4	1,2,3...16	a+b
32P-6043-041V-9	85011-0153	yes	1	----- 2	1,2,3...16	a+b
32P-6043-042V-7	85011-0141	yes	2	Wire wrap 13,3	1,2,3...16	a+b
32P-6043-042V-8	85011-0139	yes	2	Wire wrap 9,4	1,2,3...16	a+b
Engineering number	Ordering code	Molex std.	Perform.level hard gold acc.MIL-G45204	Termination / L	Contact sequence / row	

		FIRST ANGLE PROJECTION <input type="checkbox"/> <input checked="" type="checkbox"/>		REVISE ONLY ON CAD SYSTEM		2	A
REVISIONS	DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2		DRWG BY Ca	CAD/CAM FILENAME 612b3202 dgn	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
	INCH (METRIC)		CHK'D BY	TITLE 32 pos. Male connector acc. DIN 41612 style Q/2 (C-Pin) / Ordering code			
	3 PLACE ± .		APP'D BY <i>No.</i>				
	2 PLACE ± .	±	SCALE		SHEET NO. DATE 20F3 94/02/07		
1 PLACE ±	±	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		PART NO. DWG NO. SIZE SEE CHART 612-6043-202 D			
DESIGN DIMENSION <input checked="" type="checkbox"/> (MM)		EQUIVALENT DIMENSION <input type="checkbox"/> (MM)					
(PRIMARY) <input type="checkbox"/> IN.		(SECONDARY) <input type="checkbox"/> IN.					

- 1. General : Technical Data
32pos. Male connector acc.DIN 41612 style Q/2
(C-Pin)
- 2. Material :
- 2.1 Moulding material : Thermoplastic Polyester GV30 grey RAL 7032
- 2.1.1 Moulding material
burning properties acc. to UL94 V0
- 2.1.2 Resistance against
solvents : good
- 2.2 Pin contact : CuSn
- 2.2.1 Contact plating : Performance level I or II (Test acc.DIN 41612 part.5)
- 3. Printing : Part.No., date of manufacturing

Sheet	Dwg Issue	Date	Name	Change	Remark
1	Dimens. A	94/02/07	Ca
2	Ord.code A	94/02/07	Ca
3	Data A	94/02/07	Ca

Sheet 3 of 3

Umbrella index AA

M O L E X
GmbH

32pos.Male Connector
Data
612-6043-202