

## Specification Sheet

Part Number: 181-21003



Solid Wall Wiring Duct, 2" X 1", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	181-21003
----------------	-----------

Type	SD2X1
------	-------

Color	White (WH)
-------	------------

### Features & Benefits

- Solid wall construction provides excellent coverage to keep wires clean.
- Durable material protects wires from damage, with long-lasting performance.
- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Available standard colors complement or contrast in light and dark environments.
- Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement (Covers to be purchased separately.)

Quantity Per	carton
--------------	--------

**Product Description**

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths.

**Short Description**

Solid Wall Wiring Duct, 2" X 1", Non-Adhesive, PVC, White, 120ft/Carton

**Global Part Name**

SD2X1-PVC-WH

**Technical Description**

Non-Adhesive

**Length L (Imperial)**

6.0

**Length L (Metric)**

1.83

**Width W (Imperial)**

2.0

**Width W (Metric)**

50.8

**Height H (Imperial)**

1.06

**Height H (Metric)**

26.90

**Mounting Hole Centers (Imperial)**

4.0

**Material**

Polyvinylchloride (PVC)

**Material Shortcut**

PVC

**Flammability**

Self-Extinguishing

**Halogen free** No

**Operating Temperature (Metric)** +122°F (+50°C)

**Reach Complaint(Article 33)** No

**ROHS Complaint** Yes

**Certification/Specification WEB** CSA EN 50085-1:2005 + A1:2013 UL EN 50085-2-3\_1A

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 120

**Package Quantity (Metric)** 36.58

**Customs Number** 3925900000