

**SAC-3P-M12Y/2XM 8FS VP**

Order No.: 1683549

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1683549>Y-distributor/connector M12, with female connector M8, 3-pos.  
connector (parallel)**Commercial data**

EAN	4017918166946
Pack	5 pcs.
Customs tariff	85366990
Weight/Piece	0.0133 KG
Catalog page information	Page 104 (PC-2009)

**Product notes**WEEE/RoHS-compliant since:  
01/01/2008

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General data**

Nominal current $I_N$	4 A
Nominal voltage $U_N$	60 V
Number of positions	3
Volume resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 10 \text{ G}\Omega$

Ambient temperature (operation)	-25 °C ... 90 °C
<b>General characteristics</b>	
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65/IP67
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Status display	No

#### Certificates / Approvals




Certification


GOST

#### Diagrams/Drawings

Dimensioned drawing




Circuit diagram




Contact assignment of the M12/M8 Y distributor

Schematic diagram



Pin assignment M12 plug, 3-pos., A-coded, view male side



Pin assignment M8 socket, 3-pos., view female side

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;